



REDOIL

TECHNICAL DATA SHEET



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

UNIAGRI 10W STOU

STOU agricultural and earthmoving machinery lubricant

SPECIFICS

API CF/ CF-2

CAT TO-4

Allison C-4

KOMATSU kes 07.868.1 (hydraulic systems for earth-moving machines)



TECHNICAL DESCRIPTION

Special Multifunctional STOU Lubricating Fluid is characterised by an atypical viscosity grade for this category. It is specifically designed for use in diesel engines of agricultural machinery, in accordance with the user and maintenance manuals of the respective manufacturers, which specify lubricants with low viscosity and a SAE 10W grade.

In addition to its engine-oil function, the product's multifunctional STOU technology, approved by leading manufacturers of agricultural machinery, enables the simultaneous lubrication of the engine unit and transmissions, differentials, wet brakes, drive pulleys, mechanical guides, lifters, transmission components, and hydraulic systems in general.

The use of this product ensures the following benefits:

- Anti-oxidation function to counteract the molecular oxidation of the lubricant;
- Maximum thermal stability;
- Maximum dispersing power;
- Extended oil change intervals;
- Maximum cleaning power;
- High dispersant, anti-corrosion, and anti-rust properties.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

UNIAGRI 10W STOU

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	Kg/dm ³	ASTMD7042	0,865
Viscosity 40°C	cSt	ASTMD445	33
Viscosity 100°C	cSt	ASTMD445	6,3
Viscosity Index	-	ASTMD2270	145
Flash Point	°C	ASTMD92	212
Freezing point	°C	ASTMD97	-40

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet.
Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio