



REDOIL

SISTEMI DI
GESTIONE CERTIFICATI
COY
CERTIQUALITY
UNI EN ISO 9001:2015
UNI EN ISO 14001:2015



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

ATF DEXRON II

Lubricant for automatic transmissions

SPECIFICS

GM DEXRON IID MAN 339 Z1, V1
ALLISON C3 MB 236.3
ZF TE-ML 03D, 04D, 09, 11, 14A, 17C



TECHNICAL DESCRIPTION

High viscosity index mineral formulation specifically for low ratio automatic transmissions, hydraulic transmissions, power steering, torque converters and manual transmissions requiring Dexron IID performance levels. Maximum performance is guaranteed under the most severe conditions of use at all speeds at all temperatures and throughout the life of the lubricant. The special additive limits gear deterioration and limits the coefficient of friction between moving parts, preventing vibration and noise. It is not aggressive towards rubber and metal seals.

The use of this product ensures

- High thermal and oxidative stability;
- Maximum resistance to wear;
- Maximum compatibility with the materials used in these systems;
- Low creep point;
- Immediate control response even at low temperatures;
- Maximum cleaning action;
- Maximum anti-foaming action;
- High anti-corrosion and anti-rust properties.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL

TECHNICAL DATA SHEET

ATF DEXRON II



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Red
Appearance	-	Visual	limpid
Density	Kg/dm ³	ASTMD7042	0,857
Viscosity 40°C	cSt	ASTMD445	43
Viscosity 100°C	cSt	ASTMD445	7,5
Viscosity Index	-	ASTMD2270	141
Flash Point	°C	ASTMD92	222
Freezing point	°C	ASTMD97	-40

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio