



REDOIL

TECHNICAL DATA SHEET

ATF HYBRID

Lubricant for automatic transmissions

SPECIFICS

NISSAN MATIC S D/J/K TOYOTA WS TOYOTA T-II/T.IV
HONDA ATF -DW MAZDA ATF-MIII/MV/D2
HYUNDAI SP-IV KIA ISUZU
MITSUBISHI ATF-J3 SPII/SP III SUZUKI AT 5D06 SUBARU ATF ATF/HP
DAIHATSU AMMIX ATF DII / ATF DIII SAAB 93 160 393

TECHNICAL DESCRIPTION

A synthetic formulation with a high viscosity index and extremely stable friction characteristics to ensure controlled slippage of all mechanical and transmission components. Specifically designed for high-ratio automatic transmissions fitted in Japanese and Asian vehicles. The special additive technology ensures maximum performance of the soft synchromesh under the most severe conditions of use at all speeds at all temperatures and throughout the life of the lubricant.

The use of this product ensures

- Very high thermal and oxidative stability;
- Exceptional friction control;
- Maximum resistance to wear;
- Maximum compatibility with materials used in these systems;
- Low pour point;
- Immediate control response even at low temperatures;
- Maximum cleaning action;
- Maximum anti-foaming action;
- High anti-corrosion and anti-rust properties.

For further details, please contact the technical department.



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

ATF HYBRID

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	Kg/dm ³	ASTMD7042	0,852
Viscosity 40°C	cSt	ASTMD445	34
Viscosity 100°C	cSt	ASTMD445	7,0
Viscosity Index	-	ASTMD2270	173
Flash Point	°C	ASTMD92	223
Freezing point	°C	ASTMD97	-43

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio