



REDOIL

TECHNICAL DATA SHEET

ATF DEXRON VI

Lubricant for automatic transmissions

TECHNICAL DESCRIPTION



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY

Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024



A high-tech synthetic formulation with universal characteristics due to the special additive chemistry with low viscosity gradation and extremely stable friction values. Specifically for high-ratio automatic transmissions, sequential transmissions, automatic transmissions with electronic clutch control, power steering, torque converters and manual transmissions requiring Dexron VI performance levels. Maximum performance is guaranteed under the most severe conditions of use at all speeds at all temperatures and throughout the life of the lubricant. The special additive limits the deterioration of the gears and by appropriately modifying the friction generates a smooth engagement of the automatics avoiding vibrations and noise. It is not aggressive towards rubber and metal seals.

The use of this product ensures

- Very high thermal and oxidative stability;
- Exceptional friction control;
- Maximum resistance to wear;
- Maximum compatibility with materials used in these systems;
- Low pour point;
- Immediate control response even at low temperatures;
- Maximum cleaning action;
- Maximum anti-foaming action;
- High anti-corrosion and anti-rust properties.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

ATF DEXRON VI

Lubricant for automatic transmissions

SPECIFICS

AUDI	G055 005-G055 162-G055 540 -G060162 -G060540A2-G052533-G053001A2-G053001
BMW	ATFVI - ATF3 + 83229407858-8322289720-83220403249-83222163514-83222289720- BMW LA2634 BMW LT71141 MINI-ATF VI
BMW	83220397114-83220142516-83220142516-83222355599-83220432807-83222152426 83222413477-83229400275-83222305396-83222355601-83222305397-83220403248 83229407738-
CHRYSLER	DEXRON VI - MS90030-A5 -ATFIII+ -ATFIV+
FIAT	TYPE IV 9,55550-AV5- FIAT 9,5555-AV-6
FORD	MERCON M2C116-H M2C922-A1 M2C138-CJ M2C938-A M2C924-A4
GM	DEXRON VI DEXRON IID DEXRON IIIG DEXRON IIHH GM DEXRON HP ATF GM DEXRON ULV GM1940184 GM88861003 GM 9986333 GM 93165414
HONDA	ATF DW-1 ATF-Z1 ATF TYPE-3 HONDA 0826699907 HONDA 0820009001 HONDA 082009005 HONDA 082009017 HONDA 82669904
HYUNDAI	SP-IV SP-III SP-IV M/RR
JAGUAR LR	ATF JLR 20238 JF8432 JLR 20292 02JDE 26444 JLR ATF JLM- LR 023288 TYK 500050 LR023289
KIA	SP-IV / IV.RR-
MERCEDES BENZ	MB 236.17 MB 236.12 MB 236.14 MB 236.16 MB 236.15 MB ATF -FLUID MB 236.7 MB 236.8 MB 236.41
MAZDA	A7/ ATF D-II / M-III/ M-V/FSN/-1-
NISSAN	MATIC-S MATIC J/D /K /P/S/W
PEUGEOT	PSA B712340 PSA AW-1 PSA EAT6-
PORSCHE	PORSCHE ATF-VI PORSCHE 00004330400-
SUZUKI	ATF-2384K ATF 3317 ATF 2326 ATF 3314 ATF 3309-
SUBARU	ATF HP ATF 5AT-
TOYOTA	ATFWS TOYOTA D-II/D-III/ T-III/T-IV-
VOLKSWAGEN	G055540 G060162 G055162 G055025 G055005 G052590 G052025 G052055 G052162 G052990 G053001 G053025-
ZF LIFEGUARDFLUID 5 ZFS671090170 ZF LIFEGUARDFLUID 6 ZF S671090255	



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 - NOLA (NA) - ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL

TECHNICAL DATA SHEET

ATF DEXRON VI



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Red
Appearance	-	Visual	limpid
Density	Kg/dm ³	ASTMD7042	0,848
Viscosity 40°C	cSt	ASTMD445	29
Viscosity 100°C	cSt	ASTMD445	6,05
Viscosity Index	-	ASTMD2270	162
Flash Point	°C	ASTMD92	222
Freezing point	°C	ASTMD97	-51

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio