



REDOIL

SCHILDA TECNICA

ATF FLUITRONIC MULTI F2

SPECIFICHE



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

Fully synthetic lubricant for automatic transmissions, specifically designed to meet the new needs of multifunctionality that characterize the technological innovations of the new automatic transmission systems. The multifunctionality of the fluid for automatic transmissions increasingly represents a strategic key to address in a structured way the new challenges of competitiveness that through these very versatile and highly compatible products we can have. Warehouse stocks represent a cost for the company and the new transmission systems increasingly numerous require the purchase of an ever greater number of dedicated lubricants, it is clear that by optimizing the management of stocks with multifunctional products we obtain a higher quality of operation with a notable reduction in waste.

DESCRIZIONE TECNICA

The use of this product ensures:

Very high thermal and oxidative stability

Maximum energy efficiency

Fluid couplings

Maximum wear resistance

Maximum compatibility with the materials used in these systems

Low pour point

Maximum detergent action

Maximum anti-foam action

High anti-corrosion and anti-rust properties

For further details, contact the technical office



Via Boscofangone, Zona industriale ASI

80035 – NOLA (NA) – ITALIA

Tel: 081 3151396/97

Fax: 081 3151605

Web: www.siralspa.it

laboratorio@siralspa.it



Responsabile di laboratorio



REDOIL



SCHEDA TECNICA

ATF FLUITRONIC MULTI F2

Caratteristiche Tipiche

Proprietà	Unità	Metodo	Valori Medi
Colore	-	Visivo	Rosso
Aspetto	-	Visivo	limpido
Densità	Kg/dm ³	ASTMD7042	0,846
Viscosità 40° C	cSt	ASTMD445	33,8
Viscosità 100° C	cSt	ASTMD445	7
Indice di viscosità	-	ASTMD2270	175
Flash Point	°C	ASTMD92	216
Punto di congelamento	°C	ASTMD97	-47

MODALITA' D'USO

Utilizzare secondo le raccomandazioni riportate nel libretto d'uso e manutenzione fornito dal produttore. Conservare il prodotto in luogo fresco e asciutto, al riparo dai raggi diretti del sole e a temperature non superiori ai 60°C.

SICUREZZA E AMBIENTE

Utilizzare in conformità alle raccomandazioni fornite nella Scheda di Sicurezza

Informazioni aggiuntive su MSDS



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio