



REDOIL



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANUFACTURING SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

ULTRASINT FE SAE 0W-20 HTHS >2.6

Engine lubricant PCMO Fuel economy

SPECIFICS/APPROVALS

API SP SN-PLUS
ACEA C5 C6
MB 229.71 OPEL OV 040 1547
GM DEXOS D
FIAT 9.55534-DSX
PSA B71-2010 STJLR 0.35006
FORD WSS-M2C952-A1



TECHNICAL DESCRIPTION

Synthetic lubricant based on polyalphaolefins (PAO), developed for high energy efficiency and low emission engines which require fluids with a range of 0W-20 viscosity.

The special additive formulation meets the performance requirements of hybrid engines through suitable friction modifiers that act on the control of dynamic and static values, adjusting the value to suit the driving conditions.

This innovative technology reduces fuel consumption and protects the entire mechanical system.

The use of this product ensures:

- Maximum energy efficiency and corresponding reduction in fuel consumption;
- Exceptional action against LSPI (Low-Speed Pre-Ignition);
- Low friction coefficient;
- Reduced pollutant emissions;
- Maximum oxidation stability, particularly useful under high operating temperatures reached in modern turbocharged systems;
- Low pour point and extremely high viscosity index, ensuring maximum protection even under significant temperature fluctuations;
- Excellent detergency, dispersion, anti-corrosion, and anti-rust properties.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

ULTRASINT FE SAE 0W-20 HTHS >2.6

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	Kg/dm ³	ASTMD7042	0,844
Viscosity 40° C	cSt	ASTMD445	46,5
Viscosity 100° C	cSt	ASTMD445	8,8
Viscosity Index	-	ASTMD2270	172
Flash Point	°C	ASTMD92	224
Freezing point	°C	ASTMD97	-42

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio