



# REDOIL

## TECHNICAL DATA SHEET



EELQMS

EUROPEAN ENGINE  
LUBRICANTS QUALITY

MADE IN ITALY  
Data di prima emissione  
19/11/2021

Rev. N°4 del 01/07/2024

### ULTRASINT SAE 0W-30 VW 504-507

*Engine Lubricant PCMO Fuel economy*

#### SPECIFICS/APPROVALS

ACEA C3  
VW 504.00/ VW 507.00  
PORSCHE C-30  
BMW LL-04

#### TECHNICAL DESCRIPTION

Designed specifically for VAG Group engines, this lubricant is highly regarded for its adherence to the VW 504.00/507.00 specification.

The technological contribution to the most efficient and economical use of energy is the basis for the formulation of this lubricant. Its advanced formulation makes it a high performance synthetic lubricant specifically designed for gasoline and diesel engines with exceptional energy saving, protective and anti-pollution properties.

The combination of low viscosity and specific modifiers, which control friction values in relation to driving conditions, allows this lubricant to achieve maximum fuel consumption reduction. Its uniqueness comes from its patented special additives, which are characterised by very low levels of sulphated ash (ASH), phosphorus and sulphur, as required by the VW specification to protect exhaust gas aftertreatment systems.

These innovative additive technologies ensure cleaning, dispersal and protection with long-lasting performance that exceeds the manufacturer's replacement intervals.

The use of this product ensures:

- Maximum energy efficiency and corresponding reduction in fuel consumption;
- Friction enhancer with value control;
- Reduced pollutant emissions;
- Maximum oxidation stability, particularly useful at the high operating temperatures reached in modern turbocharged systems;
- Low pour point and extremely high viscosity index, ensuring maximum protection even under significant temperature fluctuations;
- Excellent detergency, dispersion, anti-corrosion, and anti-rust properties.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI  
80035 – NOLA (NA) – ITALIA  
Tel: 081 3151396/97  
Fax: 081 3151605  
Web: [www.siralspa.it](http://www.siralspa.it)  
[laboratorio@siralspa.it](mailto:laboratorio@siralspa.it)

Responsabile di laboratorio



# REDOIL



EELQMS

EUROPEAN ENGINE  
LUBRICANTS QUALITY  
MANAGEMENT SYSTEM

Data di prima emissione  
19/11/2021

Rev. N°4 del 01/07/2024

## TECHNICAL DATA SHEET

### ULTRASINT SAE 0W-30 VW 504-507

#### *Typical characteristics*

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	Kg/dm <sup>3</sup>	ASTMD7042	0,842
Viscosity 40° C	cSt	ASTMD445	61,0
Viscosity 100° C	cSt	ASTMD445	11,3
Viscosity Index	-	ASTMD2270	182
Flash Point	°C	ASTMD92	221
Freezing point	°C	ASTMD97	-49

#### MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

#### SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI  
80035 – NOLA (NA) – ITALIA  
Tel: 081 3151396/97  
Fax: 081 3151605  
Web: [www.siralspa.it](http://www.siralspa.it)  
[laboratorio@siralspa.it](mailto:laboratorio@siralspa.it)

Responsabile di laboratorio