



REDOIL

TECHNICAL DATA SHEET

EXTRASINT SAE 5W-30 C3 VW 504-507

Engine Lubricant PCMO



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

SPECIFICS

- API SP SN SN-PLUS ACEA C3
- VW 504.00 VW507.00 TL 52195
- BMW LL-04 MB 229.31 MB 229.51 MB 229.52
- PORSCHE C30
- OPEL OV 0401547 -G30
- OPEL OV 0401547 -D30
- FIAT 9.55535 S3



TECHNICAL DESCRIPTION

High-Performance Low-Ash Lubricant specifically designed for VAG Group gasoline and diesel engines, as well as all systems equipped with direct injection, SCR/TWC catalysts for nitrogen oxide reduction and particulate filters (DPF/FAP), with or without turbochargers.

The formulation, developed by the SIRAL research team using advanced technologies and incorporating unique metallocene mPAO molecules, provides exceptional oxidative stability that fully meets the stringent long life requirements of the VW 504.00/507.00 specifications. Particularly valued for its effectiveness in controlling LSPI (Low-Speed Pre-Ignition) in gasoline direct injection (FSI) systems.

The use of this product guarantees

- Excellent oxidation stability and extended drain intervals;
- Superior LSPI prevention;
- Low friction;
- Low pour point and very high viscosity index to ensure maximum protection even under significant temperature fluctuations;
- Excellent anti-corrosion, anti-rust and detergent properties;
- Low sulphur, phosphorus and sulphate ash content.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL

TECHNICAL DATA SHEET

EXTRASINT SAE 5W-30 C3 VW 504-507



EUROPEAN ENGINE
LUBRICANTS QUALITY
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	Kg/dm ³	ASTMD7042	0,852
Viscosity 40°C	cSt	ASTMD445	65,10
Viscosity 100°C	cSt	ASTMD445	11,4
Viscosity Index	-	ASTMD2270	171
Flash Point	°C	ASTMD92	228
Freezing point	°C	ASTMD97	-37

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio