



REDOIL

TECHNICAL DATA SHEET



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

EXTRASINT SAE 5W-40 MULTIJET

Engine Lubricant PCMO

SPECIFICS

- ACEA A3/B4 API SN
- MB 229.1 MB 229.5 MB 229.52 226.5
- VW 502.00 VW 505.00
- RENAULT RN 0700 RN 0710
- PORSCHE A40
- PSA B712296
- FIAT 9.55535-M2 FIAT 9.55535-Z2 FIAT 9.55535-N2 FIAT 9.55535-H2
- GM-LL-B025
- BMW LL-01



TECHNICAL DESCRIPTION

This lubricant has been specifically formulated for turbocharged gasoline and diesel engines paired with multijet systems equipped with common-rail technology. The new formulation, created with an exclusive blend of special synthetic bases enriched with detergent, dispersant, and anti-sludge additives, is designed to meet high performance standards for a range of engine types, including naturally aspirated, turbocharged, multivalve, and multijet systems. This product meets the rigorous standards set by the engineering industry and is suitable for use in demanding and severe driving conditions, including highway use, city traffic, and all seasons.

The use of this product ensures the following benefits:

- Acid neutralisation through calcium sulfonate-based technologies;
- Excellent anti-corrosion, anti-rust, and cleaning properties;
- Maximum dispersancy;
- Maximum resistance of the lubricating film (high HTHS value);
- Outstanding resistance to viscosity increase;
- Zero evaporation.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL

TECHNICAL DATA SHEET



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

EXTRASINT SAE 5W-40 MULTIJET

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	Kg/dm ³	ASTMD7042	0,858
Viscosity 40°C	cSt	ASTMD445	89
Viscosity 100°C	cSt	ASTMD445	14,0
Viscosity Index	-	ASTMD2270	162
Flash Point	°C	ASTMD92	230
Freezing point	°C	ASTMD97	-33

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio