



REDOIL



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

EXTRASINT SAE 0W-40 C3

Engine Lubricant PCMO

SPECIFICS

ACEA C3 API SP SN-PLUS CF
MB 229.31 MB229.51 MB 229.52
BMW LL-04 GM DEXOS-2 PORSCHE C40
RENAULT RN 0700 RN 0710
FIAT 9.5555-S2



TECHNICAL DESCRIPTION

Next-Generation Low-Ash Lubricant: specifically designed to extend engine life and prolong oil change intervals in low-ash, high-energy efficiency systems. This lubricant is formulated with Group IV synthetic base oils, which minimise oxidative phenomena even under elevated operating temperatures typical of turbocharged systems. The use of low-ash additives guarantees a balance between protection, reduced emissions and maximum engine performance.

The use of this product guarantees the following benefits:

- Maximum energy efficiency and a corresponding reduction in fuel consumption;
- Low friction coefficient;
- Reduced pollutant emissions;
- Superior oxidative stability, especially useful under high-temperature conditions in modern turbocharged systems;
- Low pour point and an exceptionally high viscosity index, providing maximum protection even during extreme thermal fluctuations;
- Excellent anti-corrosion, anti-rust, and cleaning properties.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL

TECHNICAL DATA SHEET

EXTRASINT SAE 0W-40 C3



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	Kg/dm ³	ASTMD7042	0,859
Viscosity 40°C	cSt	ASTMD445	90,50
Viscosity 100°C	cSt	ASTMD445	15,12
Viscosity Index	-	ASTMD2270	177
Flash Point	°C	ASTMD92	229
Freezing point	°C	ASTMD97	-40

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio