



REDOIL



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

Data di prima emissione
07/03/2024

TECHNICAL DATA SHEET

EXTRASINT 5W-30 RN-17

Engine Lubricant PCMO

SPECIFICS

- ACEA C3 API SN
- RENAULT RN17 RN0700/0710
- MB 226.52

TECHNICAL DESCRIPTION

Synthetic Lubricant: specifically designed for use in next-generation turbocharged gasoline and diesel engines equipped with exhaust gas after-treatment systems. With excellent oxidation resistance and superior heat control capabilities, this product is perfectly compatible with Renault engine systems requiring the RN-17 specification.

The use of this product ensures the following benefits:

- Excellent oxidation stability, particularly useful at the high operating temperatures reached in modern turbocharged systems;
- Low pour point and exceptionally high viscosity index, providing maximum protection even during significant thermal fluctuations;
- Superior anti-wear performance for all types of metals and alloys, reducing friction coefficients and enabling lower energy consumption;
- High-level anti-corrosion, anti-rust, and cleaning properties.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

Data di prima emissione
07/03/2024

TECHNICAL DATA SHEET

EXTRASINT 5W-30 RN-17

Typical characteristics

| Properties | Unit | Method | Average values |
|-----------------|--------------------|-----------|----------------|
| Colour | - | Visual | Amber |
| Appearance | - | Visual | Limpid |
| Density | Kg/dm ³ | ASTMD7042 | 0,855 |
| Viscosity 40°C | cSt | ASTMD445 | 67,0 |
| Viscosity 100°C | cSt | ASTMD445 | 11,5 |
| Viscosity Index | - | ASTMD2270 | 167 |
| Flash Point | °C | ASTMD92 | 229 |
| Freezing point | °C | ASTMD97 | -36 |

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio