



REDOIL

TECHNICAL DATA SHEET



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

SINT SAE 10W-40

Engine Lubricant PCMO

SPECIFICS

ACEA A3/B4 API SN/CF
MB 229.1 MB 229.3 MB 229.5 MB 226.5
VW 501.00 VW 502.00 VW 505.00
RENAULT RN0700 RN0710 PSA B712300
FIAT 9.55535-G2



TECHNICAL DESCRIPTION

Hydroisomerised GPIII Lubricant has been specifically developed to provide superior protection and ensure exceptional performance in next-generation gasoline and diesel engines. The additive composition of this product guarantees maximum protection of internal engine surfaces, offering excellent stability, dispersancy, detergency, and extended oil change intervals.

At high temperatures, it provides superior protection compared to high-viscosity oils, ensuring the safety required to meet the demands of the latest high-performance engines. Similarly, it ensures excellent fluidity at low temperatures and improved operational efficiency.

The use of this product ensures the following benefits:

- Effective counteraction to the molecular oxidation of the lubricant;
- Maximum thermal stability;
- Extended oil change intervals;
- Superior detergency;
- High-level dispersant, anti-corrosion, and anti-rust properties.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL

TECHNICAL DATA SHEET



EELQMS

EUROPEAN ENGINE
Lubrificazione di prima emissione
MANAGER 19/11/2022

Rev. N°4 del 01/07/2024

SINT SAE 10W-40

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	Kg/dm ³	ASTMD7042	0,86
Viscosity 40°C	cSt	ASTMD445	93,6
Viscosity 100°C	cSt	ASTMD445	14,1
Viscosity Index	-	ASTMD2270	155
Flash Point	°C	ASTMD92	231
Freezing point	°C	ASTMD97	-31

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio