



REDOIL

TECHNICAL DATA SHEET

SINT SAE 15W-50

Engine Lubricant PCMO



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

SPECIFICS

ACEA A3/B4 API SN CF
MB 229.1
VW 501.01 VW 505.00



TECHNICAL DESCRIPTION

This special multigrade lubricant provides unparalleled performance by combining synthetic and hydrogenated mineral base technologies with a new category of additives that have been specifically tested to meet the specifications required by the latest engine technologies. This product ensures excellent lubrication, enhances engine efficiency, improves cleanliness, and provides superior protection during critical operating phases.

The use of this product ensures the following benefits:

- Effective counteraction against the molecular oxidation of the lubricant;
- Sealing action to prevent leaks and reduce oil consumption;
- Extended oil change intervals;
- Maximum detergency;
- Superior dispersancy, anti-corrosion, and anti-rust properties.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

SINT SAE 15W-50

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	Limpid
Density	Kg/dm ³	ASTMD7042	0,865
Viscosity 40°C	cSt	ASTMD445	141
Viscosity 100°C	cSt	ASTMD445	18,5
Viscosity Index	-	ASTMD2270	148
Flash Point	°C	ASTMD92	233
Freezing point	°C	ASTMD97	-26

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio