



REDOIL



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY

Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

MTF 75W

Manual transmission lubricant

SPECIFICS

API GL-4 BMW/MINI 83220306816 83220397244 83222409710 MTF-LT-3 DTF-1
CITROEN JWS2271 1618078480
FORD WSS-M2C200-D2/D3/E1 FORD C-MAX MONDEO S-MAX TRANSIT FOCUS HONDA MTFIII
FIAT 9.55550-MZ6
MB 235.73 MB 235.10 PSA B71 2316 PSA B71 2317
VOLVO C30/C70 S40/60 V50/70 1161839 1161838
VW TL 521-71 VW TL 521-78 VW TL G052 171-A1 G052 178 A2 G052 512 A2
VW TL 726 G052726A2 G055726A2 G060726A2 G070726A2

TECHNICAL DESCRIPTION

Fluid created through the use of innovative technologies that offer exceptional advantages in terms of performance, protection and fuel economy.
Particularly suitable for manual gearboxes, it is able to generate maximum performance in heavy-duty conditions even in extreme climatic conditions.
The unrivalled low-viscosity synthetic formulation provides excellent cold flow properties that extend synchroniser life and significantly improve shift quality.

The use of this product ensures:

- Optimised shifting performance;
- Maximum shear stability;
- Maintenance of viscosimetric gradation over the entire service life;
- Very high thermal and oxidative stability;
- Exceptional friction control;
- Maximum compatibility with materials used in these systems;
- Low pour point;
- Immediate control response even at low temperatures;
- Maximum cleaning action;
- Maximum anti-foaming action;
- High anti-corrosion and anti-rust properties.

For further details, please contact the technical department



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio

TECHNICAL DATA SHEET

MTF 75W

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	Kg/dm ³	ASTMD7042	0,852
Viscosity 40°C	cSt	ASTMD445	30
Viscosity 100°C	cSt	ASTMD445	6,1
Viscosity Index	-	ASTMD2270	156
Flash Point	°C	ASTMD92	221
Freezing point	°C	ASTMD97	-52

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.