



REDOIL



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

Data di prima emissione
07/03/2024

TECHNICAL DATA SHEET

UTENSIL 220

Slide and slide lubricant

SPECIFICS/APPROVALS

- DIN 51502 CGLP
- ISO 6743-13 ISO 19378 ISO-L-GB ISO-L-GA
- ISO 6743-6 ISO 12925-1 ISO-L-CKC ISO-L-CKE
- ISO 6743-4 ISO 11158 ISO -L-HM
- CINCINNATI MILACRON P50 (ISO VG 220)
- STANIMUC G 220



TECHNICAL DESCRIPTION

High-quality, multifunctional hyper-tech fluid for both circulation and leakage systems, specially designed and developed for hydraulic and load applications applied to the lubrication of machine tool guides and slides, operating machines, lifts and lifts.

The combination of hydrogenated mineral bases and the special additive package provides exceptional grease and anti-friction properties on a wide range of slide materials, including steel-on-steel and steel-on-polymer, reducing noise and stick-slip, which is characterised by sticking and shaking especially when sliding at low speeds.

The additive package also provides the lubricant with strong anti-wear, anti-rust, anti-oxidising, excellent adhesion (anti-drip) and high load resistance properties.

The use of this product ensures

- Multifunctionality (combination of the guide function with the hydraulic and gear function);
- Anti-drip;
- Anti-friction;
- No stick-slip;
- EP protection.

For further details, please contact the technical department



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio

TECHNICAL DATA SHEET

UTENSIL 220

Typical characteristics

Properties	Unit	Method	Average values
Density at 15°C	Kg/m ³	ASTM D 1298	878
Kinematic viscosity at 40°C	cSt	ASTM D 445	220
Kinematic viscosity at 100°C	cSt	ASTM D 445	20.1
Viscosity index	-	ASTM D 2270	105
Flash Point	°C	ASTM D 92	230
Pour Point	°C	ASTM D 97	-20

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet.
Additional information on MSDS.