



REDOIL

TECHNICAL DATA SHEET



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

COMPETITION GT4 10W-60

Four Stroke Motorcycle Lubricant

SPECIFICS

- API SP/ SN/SM
- JASO T903 JASO MA-MA2
- JASO Quality Category SP

TECHNICAL DESCRIPTION

Special fluid of viscosimetric grade 10 Winter, for 4T motorbike engines of the COMPETITION GT4 category, characterised by high HTHS values. Specific for racing and competition applications of large displacement motorbikes with or without wet clutches, jet skis, snowmobiles, SXS and ATVs, to be used according to the viscosimetric gradations given in the manufacturers' user and maintenance manuals. Engineered in SIRAL's development and design laboratories, it identifies its greatest asset in its ability to generate optimum friction according to engine rpm and driving style. This unique feature gives the product extensive multi-functionality precisely because it is capable of generating high friction in motorbikes with oil bath clutches that require a JASO MA and low friction in scooters that do not have oil bath clutches and require low friction values for better lubricity. Based on the combination of these multi-functional characteristics together with those of durability, protection and cleanliness, it is particularly suitable for all types of four stroke motorbikes.

The use of such a product ensures:

- Anti-hopping function for improved clutch control;
- Exceptional catalyst protection (low phosphorous and sulphur content JASO MA-2);
- Smooth gear engagement,
- Maximum heat dissipation;
- Excellent oxidation stability and extension of oil changes;
- High pre-ignition counteracting action;
- Low friction;
- Low pour point and very high viscosity index, ensuring maximum protection even with extreme temperature fluctuations;
- High anti-corrosion and anti-rust cleaning properties;
- Low sulphur phosphorus and sulphated ash content.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

COMPETITION GT4 10W-60

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	Kg/dm ³	ASTMD7042	0,863
Viscosity 40°C	cSt	ASTMD445	191,7
Viscosity 100°C	cSt	ASTMD445	24
Viscosity Index	-	ASTMD2270	155
Flash Point	°C	ASTMD92	233
Freezing point	°C	ASTMD97	-28

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio