



REDOIL

TECHNICAL DATA SHEET

LONG LIFE SINTEX 10W-40 CNG-TRUCK

Engine Lubricant Heavy-Duty Diesel CNG Oil HDDO heavy-duty traction



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

SPECIFICS

API CK-4/ CJ-4/CI-4+/CI-4/CH-4 ACEA E11/E9/E8/E6/E4
DTFR15C100 (MB 228.31), DTFR15C110 (MB 228.51), DTFR15C120 (MB 228.52)
DETROIT 93 K222 SFU IVECO 18-1804 TLS CK4
CATERPILLAR ECF-3 SCANIA LA
MAN 3271-1/3477/3775 VOLVO VDS-4.5 VOLVO CNG
MACK E0S 4.5 RENAULT RVI RLD-3 / RLD-4
CUMMINS CES 20081/ CES20086 JASO DH-2
DEUTZ DQC III-10-LA/DQC IV-18-LA MTU CAT Type 2.1/3.1
SFU IVECO CAT TLS CK-4 IVECO 18-809 CLASSE NG2



TECHNICAL DESCRIPTION

A special synthetic lubricant for diesel and gas engines in commercial vehicles, designed to meet enhanced performance requirements, offering excellent control of piston cleanliness, wear, soot, and stability. It is recommended for diesel engines equipped with exhaust after-treatment systems that meet Euro I, Euro II, Euro III, Euro IV, Euro V, and Euro VI emission standards, operating under extremely severe conditions and with significantly extended oil drain intervals in accordance with the manufacturer's recommendations.

The use of this product ensures the following benefits:

- Maximum action against the molecular oxidation of the lubricant;
- Effective prevention of deposit formation;
- Maximum thermal stability;
- Extended oil change intervals;
- Maximum detergency;
- High dispersancy, anticorrosion, and antirust properties.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM

Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

LONG LIFE SINTEX 10W-40 CNG-TRUCK

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	Kg/dm ³	ASTMD7042	0,862
Viscosity 40°C	cSt	ASTMD445	96,0
Viscosity 100°C	cSt	ASTMD445	15,0
Viscosity Index	-	ASTMD2270	164
Flash Point	°C	ASTMD92	231
Freezing point	°C	ASTMD97	-30

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio