



REDOIL

TECHNICAL DATA SHEET

YELLOW FREEZE PURE

Pure cooling fluid

SPECIFICS

CUNA NC 956-16 VW G-12++
BS 6580 FK Helf R 443 AFNOR R 15/601 CUMMINS 90T8-4 /85T8-2
ASTM D 3306 ASTMD 4985 SAE J 1034 JIS K 2234 UNE26361-88
EMPA E/L 1415 MIL Italy
KSM 2142 NATO S 759
VW TL 774 D/F/G (G12 G12+ G12++) VAG (AUDI-SKODA-SEAT-PORSCHE)
MERCEDES MB 325.3 RENAULT 41-01-001
MAN 248/324 Type SNF IVECO
FORD WSS-M97B44-D / ESD M 97 B49-A / ESE M97B49-A FIAT 9.55523
CRYSLER MS 9176 OPEL GM QL 130100 GM 1899M
NAVISTAR B-1 Type III VOLVO JOHN DEERE H 24 B1 and C1
Leyland Trucks LTS 22 AF 10 Mack 014GS17004 PEGASO GM US 6277 M C
Deutz/MWN 0199-2091 WARTSILIA 32-9011

TECHNICAL DESCRIPTION

Pure permanent antifreeze fluid based on monoethylene glycol, specifically designed for heat engine cooling circuits requiring OAT (Organic Acid Technology) fluids. Particularly suitable for engines made of aluminium alloys and light metals, it represents the evolution of cooling fluid technology that accompanies the forms of engineering renewal that have taken place in the engine world.

BENEFIT

- Maximum protection of aluminium alloy engine circuits;
- High thermal dissipation capacity;
- Tracer presence for quick detection of leaks in the circuit;
- Excellent protection of the water pump and all rubber parts;
- Maximum ebullient rise;
- Long life function (maximum durability);
- NAP free (nitrate amine phosphate free).

For further details, please contact the technical department



Data di prima emissione
07/03/2024



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio

YELLOW FREEZE PURE*Typical characteristics*

Properties	Unit	Method	Average values
Colour	-	ASTMD3306	Yellow
Appearance	-	ASTMD3306	Limpido
Density	Kg/dm ³	ASTMD3306	1,13
Ph dil 50%	-	ASTMD3306	8,4
Boiling time	°C	ASTMD1120	197
Freezing time dil 50%	°C	ASTMD1177	-36
Glass corrosion testing	mg/provino	ASTMD1384	pass

*the above data represent the average production values.

% Weight ethylene glycol	Freezing time °C
4	-1,3
10	-3,5
16	-6,3
20	-8
26	-12,2
30	-15,1
36	-20,1
40	-24,1
46	-31,2
50	-36,4

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.