



REDOIL



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY

Data di prima emissione
07/03/2024

TECHNICAL DATA SHEET

HIDRUS 68

Mineral lubricant GPII+

SPECIFICS

- ISO VG 68 ISO-L-HM
- DIN 51524 PART teil 2-HLP ISO 6743-4 HM
- US PARKER DENISON HF-0/HF-1/HF-2 Level
- AFNOR NFE 48603 HM NFE 48691
- EATON VICKERS I 286-S/ EATON VICKERS M 2950-S
- FIVES CINCINNATI MILACRON P-69 (ISO VG 68) FORD M-6C32
- BOSH REXROTH RDE 90220-1/11.02 ATOS TABLE P002-E ATOS TABLE P002-1
- THYSSEN TH-N 256-142 U.S. STEEL 127-126-136
- SAWER -DANFOSS 520L0463 GM LS-2 GENERAL MOTORS LH-04-1 LH-06-1 LH-15-1
- LINDE AISE 127 METSO VDMA 24318 DANIELI HYDRAULICS CETOP RP91-HM



TECHNICAL DESCRIPTION

Hydraulic fluid formulated with GPII+ mineral bases suitably blended with innovative additives that fully meet the stringent requirements of modern fluid-dynamic technology. The viscosimetric stability tested by the resistance values under maximum stress conditions together with the strong anti-wear, anti-foaming and demulsibility properties make this product a technological excellence particularly appreciated in all hydraulic applications characterised by strong temperature and pressure ranges.

Compatible with all types of material commonly used as gaskets or jointing elements in both new and old hydraulic circuits.

The use of this product ensures:

- Maximum oxidation stability;
- Excellent thermal stability;
- Hydrolytic stability;
- Excellent material compatibility;
- High anti-corrosion and anti-rust properties;
- High anti-foaming capacity;
- Excellent pumpability at low temperatures.

For further details, please contact the technical department



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio

TECHNICAL DATA SHEET

HIDRUS 68

Typical characteristics

Properties	Unit	Method	Average values
Density at 15°C	Kg/m ³	ASTM D 1298	867
Kinematic viscosity at 40°C	cSt	ASTM D 445	68
Kinematic viscosity at 100°C	cSt	ASTM D 445	9,5
Viscosity index	-	ASTM D 2270	118
Flash Point	°C	ASTM D 92	229
Pour point	°C	ASTM D 97	-33

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.